

MultiSync® LT80™ and LT100™



Designed and equipped for remarkable portability

Excellent image quality and brightness

Outstanding ease-of-use plus full-feature remote control

The ultra-portable MultiSync® LT Series projectors are the premier solution for making powerful presentations on the road.

Continuing the NEC Technologies legacy of outstanding image quality, ease of use and reliability, the new MultiSync LT Series single-chip DLP projectors are an ultraportable solution for making powerful presentations. With exclusive NEC Technologies features, the MultiSync LT Series projectors stand out as the projectors of choice for sales automation efforts aimed at boosting productivity. Smaller than a briefcase, the MultiSync LT Series projectors are perfect traveling partners for anyone who makes presentations on the road, including sales representatives, consultants and marketing professionals.

Designed and equipped for true portability.

The MultiSync LT Series projectors are the ultra-portable projection solution for the professional on the go. They easily fit under the airplane seat in front of you, so you can take them wherever business takes you, with no hassles. Their sturdy construction includes a convenient handle integrated into the unit. And, a padded carrying case is included to ensure that your investment is protected. Other optional cases are available to provide extra protection during travel or shipping. For added convenience, the MultiSync LT100 projector offers an optional PC Card Viewer so you can store and transport your presentation on a PCMCIA card and leave your laptop behind.

High brightness and accurate, lifelike color.

The MultiSync LT Series projectors produce accurate, lifelike images using an entirely digital projection system. Texas Instruments single-chip DLP technology creates seamless images with a

higher perceived resolution than that of other projection technologies. And, its digital gray scale and color reproduction results in lifelike color images with exceptional accuracy. Additional image enhancements offered on the MultiSync LT100 projector include a 2X color wheel that reduces flicker, and excellent video quality due to the unique comb filter technology.

High-resolution images without loss of data.

Using NEC Technologies AccuBlend™ intelligent pixel blending technology, the MultiSync LT Series projectors deliver superior high-resolution images. Unlike competitive technologies that result in

a significant loss of data, AccuBlend is an intelligent compression technology that blends and remaps input data to match the available pixels on the DLP chip. Other technologies simply drop pixels or lines of information, resulting in a visible absence of information that can obscure important parts of your presentation.

Outstanding ease of use featuring total remote control. Because the MultiSync LT Series projectors are remarkably easy to use, you can concentrate on your message instead of your display technology. The MultiSync LT Series projectors include a full-featured remote control with built-

	MultiSync LT80	MultiSync LT100
Brightness	600 ANSI lumens	1000 ANSI lumens
Resolutions supported	640 × 480–1024 × 768 w/ AccuBlend	640 × 480–1280 × 1024 w/ AccuBlend
Included remote control	Yes <i>Integrated mouse lets you control your computer and presentation</i> <i>Built-in laser pointer</i>	Yes <i>Integrated mouse lets you control your computer and presentation</i> <i>Built-in laser pointer</i> <i>360° infrared system for use from anywhere in the room</i>
Manual zoom	Yes	Yes
Flexible outputs including audio	Yes	Yes
Integrated carrying handle	Yes	Yes
Adjustable front feet	Yes	Yes; plus rear adjustable feet
InstaCare 24 hour replacement service	Yes 2 years	Yes 2 years



Smaller than a briefcase, the ultra-portable MultiSync LT Series is a powerful solution for the mobile professional.



in laser pointer that enables quick, one-button access to important features. The remote control also provides access to helpful, intuitive on-screen controls that you can easily navigate using the integrated mouse. On-screen controls include:

Image adjustments including brightness, color, contrast, sharpness and position.

Customized settings that enable you to create and store up to five different settings. There's no need to re-adjust image settings every time you connect a different source. Just plug in the source, select your customized setting and begin! This feature saves time when you are using more than one source in the same presentation, because there are no interruptions to re-adjust brightness or contrast for each source.

Lamp timer that displays how many hours the lamp has been used, helping you anticipate and manage maintenance of the projector.

Language select feature, which allows you to select the language in which the on-screen menus appear.

In addition, the MultiSync LT80 comes with an introductory video and the MultiSync LT100 comes with an introductory CD-ROM that provides a hands-on demonstration of key features. Users can review the demo at their own pace, eliminating the need for corporate training.

Compatibility so broad, you just plug in and play. The MultiSync LT Series projectors offer quick and easy connection via a comprehensive input panel, which includes audio, computer, video and S-Video inputs. The included VGA cable and Macintosh® multimode adapter enable you to simply plug in and play. And, because the cable is an industry standard, you can replace it easily if you forget it or lose it on the road. The

MultiSync LT Series projectors are compatible with most common video standards in use today including NTSC, PAL, SECAM and NTSC 4.43. Plus, their universal power supply enables global companies to use the same projector model throughout their organizations.

Unbeatable peace of mind with an exclusive service warranty. NEC Technologies exclusive InstaCare™ service ensures you won't be stranded



on the road with a projector that's not performing. InstaCare guarantees a replacement projector within 24 hours or repairs on your original projector within 72 hours. NEC Technologies pays for and tracks shipping of your projector and any replacement projector via Federal Express. In addition to this convenient service, you'll have the peace of mind of knowing that your projector is backed by the responsive service and support of NEC Technologies.



The MultiSync LT Series offers the ultimate in portability. An integrated handle makes the projectors easy and convenient to carry.

MultiSync LT Series Accessories

NEC Technologies offers a full line of accessories designed to complement your MultiSync LT Series Projector.

LT TownCase

This durable case was designed for local transportation and safe storage. A front pocket provides additional safe storage for the remote control, plus any cables.



LT TownCase Plus

This case offers all of the features of the TownCase and the added convenience of a special pocket that safely stores your notebook computer.



LT AirCase This sturdy shipping case features reinforced panels, wheels and is ATA-approved for shipping via land carrier or airline. A Federal Express-approved transparent pouch stores shipping labels for added convenience.



LT Mount Sturdy, multiple-access ceiling mount features quick release capability for ease of transport plus a built-in security feature.



Replacement Lamp

A user changeable metal halide lamp. NEC recommends replacement after 1000 hours of use.



Replacement Remote Should your remote get lost or damaged, NEC offers an identical replacement remote.



PC Card Viewer Store and transport your presentation on a PCMCIA card. One memory card included. (LT100 only)



MultiSync LT80 and LT100 Specifications Model # LT80, LT100

DMD	
<i>LT80:</i>	1-Chip DMD, 800 × 600 pixel
<i>LT100:</i>	1-Chip DMD, 1024 × 768 pixel
Lens	
<i>Both Models:</i>	1.3 times manual zoom, manual focus, F2.44 F=26-30
Lamp	
<i>LT80:</i>	Metal halide lamp 270 Watt AC
<i>LT100:</i>	Metal halide lamp 280 Watt DC
Image Size	
<i>Both models:</i>	Min 24" (61cm), Max 300" (762cm)
Projection Distance	
<i>Both models:</i>	Min 3.9' (1.2m), Max 40.4' (12.3m)
Light Output	
<i>LT80:</i>	600 ANSI lumens, 1000 hour life
<i>LT100:</i>	1000 ANSI lumens, 1000 hour life
Contrast Ratio	
<i>Both models:</i>	Greater than 200:1
Color Reproduction	
<i>Both models:</i>	16,777,216 colors simultaneously
Color Temperature	
<i>LT80:</i>	5600° Kelvin
<i>LT100:</i>	7000° Kelvin
Synchronization Range	
<i>LT80:</i>	Horizontal: 15 to 60kHz (non-interlaced) Vertical: 50 to 85Hz
<i>LT100:</i>	Horizontal: 15 to 85kHz (non-interlaced) Vertical: 50 to 85Hz
RGB	
<i>Both models:</i>	Input Signals: Visual: 75 ohm 0.7Vp-positive, Sync TTL Audio: 47k ohm 0.4V rms
<i>Both models:</i>	Input Terminals: Visual: 15pin to 15pin mini D sub cable Audio: Stereo Mini Jack
<i>Both models:</i>	Output Terminals: Visual: RGB Throughout Audio: Stereo Mini Jack
PC Compatibility	
<i>Both models:</i>	640 × 480: 60, 72, 75 and 85Hz vertical refresh
<i>Both models:</i>	800 × 600: 56 to 75Hz vertical refresh
<i>LT80:</i>	1024 × 768: AccuBlend
<i>LT100:</i>	1024 × 768
<i>LT100:</i>	1280 × 1024: AccuBlend
Macintosh Compatibility	
<i>Both models:</i>	640 × 480: 60 and 67Hz vertical refresh
<i>Both models:</i>	832 × 624: AccuBlend
Video	
<i>Both models:</i>	Input Signals: Visual: S-Video Y: 75 ohm .72Vp-p, C: 75 ohm 0.28Vp-p Audio: 47k ohm 0.4V rms
<i>Both models:</i>	Input Terminals: Visual: RCA Audio: RCA x 2
<i>Both models:</i>	Horizontal Resolution: NTSC 550 lines PAL/SECAM/NTSC 4.43 350 lines

Video Compatibility	
<i>LT80:</i>	NTSC/PAL/SECAM/NTSC 4.43
<i>LT100:</i>	NTSC/PAL/SECAM/NTSC 4.43/ 3 Line Digital Comb Filter

Audio	
<i>Both models:</i>	Built-in mono speaker (1.0w, 8 ohm)

Remote Control Functions	
<i>Both models:</i>	Computer Mouse Control with left and right click buttons, Built-in Laser Pointer, Source Selection, Volume, Picture Magnification, Position, Picture Freeze, Picture Mute

On-screen Controls	
<i>Both models:</i>	Source Selection Menu: Video, S-Video, RGB Image Adjust Menu: Volume, Brightness, Contrast, Color, Tint, Sharpness, Image Mode, H Position, V Position, Auto Picture, Picture Adjust, Fine Picture Adjust Power Menu: Lamp Timer, Auto Start, Power Management Settings Menu: Custom Memory, Set Position, Language Select, Reset PC Card, White Balance, Display Mode
<i>LT100:</i>	

Fan Noise	
<i>Both models:</i>	Less than 44dB

Power Requirement	
<i>Both models:</i>	100–120v/220–240v AC, 50Hz/60Hz

Power Consumption	
<i>LT80:</i>	380W, 6.25A
<i>LT100:</i>	400W, 6.25A

Dimensions (W×H×D)	
<i>LT80:</i>	9.8" x 4.8" x 12.8" (24.8cm x 12.2cm x 32.5cm)
<i>LT100:</i>	10" x 5.8" x 13.4" (25.3cm x 14.8cm x 34.0cm)

Net Weight	
<i>LT80:</i>	9.9 lbs. (4.5kg)
<i>LT100:</i>	10.8 lbs. (4.9kg)

Supplied Accessories	
<i>Both models:</i>	Carrying Case, Wireless Remote Control with wireless mouse and laser pointer, Signal Cable, Mac Adapter, Power Cable, User's Manual, Registration Card, Quick Connect Guide
<i>LT80:</i>	Remote Mouse Receiver, Introductory Video
<i>LT100:</i>	Remote Cable, Introductory CD-ROM

Safety and Regulation	
<i>Both models:</i>	FCC: Class "A", UL 1950, CSA

Environmental Considerations	
<i>Both models:</i>	Temperature: 41°–95°F (5°–35°C), operational Humidity 30%–85%, operational

Warranty	
<i>Both models:</i>	2 year limited, parts and labor including InstaCare 24 hour replacement service
<i>Both lamps:</i>	1000 hours or 6 months, whichever comes first

For the location of the MultiSync LT dealer nearest you or for more information on MultiSync LT accessories, call **1-800-NEC-INFO**.

To speak to a MultiSync LT customer service representative, call **1-800-836-0655**.

Visit our World Wide Web home page at <http://www.nec.com>.

For more information via fax, call **NEC FastFacts™** at **1-800-366-0476** and request **Catalog #1**.

NEC Technologies, Inc.
1250 N. Arlington Heights Road, Suite 500
Itasca, Illinois 60143-1248



All specifications are the same for both models unless otherwise noted.

MultiSync is a registered trademark and LT80, LT100, AccuBlend, FastFacts and the NEC Technologies icon are trademarks of NEC Technologies, Inc. Digital Micromirror Device (DMD) and DLP are trademarks of Texas Instruments, Inc. All other brand or product names are trademarks or registered trademarks of their respective holders. All specifications are subject to change without notice. ©1998 NEC Technologies, Inc.



NEC Technologies