

3M™ Overhead Projector

Model 1885

Turn on the Light

Turn on the light with the stylish 3M™ Overhead Projector Model 1885. This deluxe overhead projector packs an articulating closed doublet lens and a maximum output of 4,300 lumens and a low of 3,600. A low-to-high dimmer switch enables the right light output for vibrant images and sharper text. Features also include such conveniences as hush-quiet fan for reduction of unwanted noise, carrying handle and fold-down post for storing and moving, digital clock for on-time meetings, and lamp changer. The 3M Overhead Projector Model 1885 has a five-year warranty on all parts and labor.



KEY FEATURES

- > Maximum output of 4,300 lumens and minimum of 3,600
- > Articulating closed doublet lens
- > Hush-quiet fan reduces unwanted noise.
- > Useful carrying handle and fold-down post provide easy storing and moving.
- > Convenient digital clock keeps track of meetings.
- > Power-cord wrap
- > Five-year warranty on all parts and labor. Please see product packaging for details of warranty terms.

ORDER NUMBER: XO-0038-0716-1 (former#: 78-9236-6597-6)

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, and dust cover

TECHNICAL SPECIFICATIONS

Specifications subject to change.

OPTICAL PERFORMANCE

- > Head: **Articulating, closed doublet** (*dual element*) lens
- > Illumination: **4,300 ANSI lumens typical** (*3,600 lumens -- low setting*)
- > Design: **Transmissive** with folded optical system
- > Stage aperture: **267 mm x 267 mm** (*10.5 inches x 10.5 inches*)
- > **Color-tuning dial**

LAMP DESCRIPTION

- > **Lamp ejector**
- > **Lamp changer**
- > Lamp Type: **FXL** (*82 volts, 360 watts*)
- > Lamp Life: **40 hours** (*high setting*), **80 hours** (*low setting*) using Model 1885

PHYSICAL CHARACTERISTICS

- > **Internal high/low switch**

ELECTRICAL FEATURES

- > **Hush-quiet fan**
- > **Digital clock**
- > Power-cord length: **4.6 m** (*15 feet*)
- > **Power-cord wrap**

MECHANICAL

- > **Lamp-interrupt switch** shuts off power to lamp when changing to prevent premature failure.
- > **Carrying handle**
- > **Fold-down post**

**Ask
about 3M
LAMPS!**

1.800.328.1371

WWW.3M.com/meetings

“Wherever there’s a great meeting, you’ll find 3M.”™

Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Presentation Solutions