

SunSplash™ DUKANE SUNSPLASH™ MODEL YEAR 2002 SUPER VALUE OVERHEAD PROJECTORS

ALL MODELS COVERED
By **DUKANE'S** EXCLUSIVE



2000 Lumen Units



MODEL #	SP2123	SP2127	SP2128	SP2133	SP2134	SP2223	SP2225	SP2226	SP2227	SP2233	SP2234
Lens Configuration	Singlet	Singlet	Singlet	2 Element	2 Element	Singlet	Singlet	Singlet	Singlet	2 Element	2 Element
Type of Head	Open	Closed	Closed	Closed	Closed	Open	Open	Open	Closed	Closed	Closed
Lens Focal Length (in.)	11.5 in.	11.5 in.	11.5 in.	14 in.	14 in.	11.5 in.	14 in.	14 in.	11.5 in.	14 in.	14 in.
Lamp Changer	No	No	Yes	No	Yes	No	No	Yes	No	No	Yes
Lumen Output	2200	2000	2000	2000	2000	2200	2200	2200	2000	2000	2000
Regular/Wide Angle	Wide Angle	Wide Angle	Wide Angle	Regular	Regular	Wide Angle	Regular	Regular	Wide Angle	Regular	Regular
Base Construction	ABS	ABS	ABS	ABS	ABS	Steel	Steel	Steel	Steel	Steel	Steel
Lamp Type	EYB	EYB	EYB	EYB	EYB	EYB	EYB	EYB	EYB	EYB	EYB
Lamp Life Hrs.	75	75	75	75	75	75	75	75	75	75	75

3000/4000 Lumen Units

New Longer Lamp Life Operation! (Lamp Life up to 250 Hours)



MODEL #	SP3127	SP3128	SP3134	SP4123	SP4127	SP4128	SP4134	SP4136	SP4234	SP4236
Lens Configuration	Singlet	Singlet	2 Element	Singlet	Singlet	Singlet	2 Element	3 Element	2 Element	3 Element
Type of Head	Closed	Closed	Closed	Open	Closed	Closed	Closed	Open	Closed	Open
Lens Focal Length (in.)	11.5 in.	11.5 in.	14 in.	11.5 in.	11.5 in.	11.5 in.	14 in.	13 in.	14 in.	13 in.
Lamp Changer	No	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes
Lumen Output	3000/2400	3000/2400	3000/2400	4000/3200	4000/3200	4000/3200	4000/3200	4000/3200	4000/3200	4000/3200
Regular/Wide Angle	Wide Angle	Wide Angle	Regular	Wide Angle	Wide Angle	Wide Angle	Regular	Regular	Regular	Regular
Base Construction	ABS	ABS	ABS	ABS	ABS	ABS	ABS	ABS	Steel	Steel
Lamp Type	ENX-5	ENX-5	ENX-5	FXL	FXL	FXL	FXL	FXL	FXL	FXL
Lamp Life (Hi/Ext) Hrs.	125/250	125/250	125/250	60/130	60/130	60/130	60/130	60/130	60/130	60/130

Common Specifications

Optical

Projection Stage Size of 10.5" x 10.5"
High Quality Fresnel Lens
Transmissive Design

Mechanical

Quiet Cooling Fan
Recessed Marker Tray
Rack and Pinion Focusing
East-West & North-South Mounting Holes for
Acetate Roll Attachment (*steel base units only*)

Electrical

120V, 60 Hz Power Operation
Permanently Attached 10' Power Cord
Cord Storage Compartment
Lamp Life (Hrs.) **EYB** 75 **ENX** High/Low 125/250 **FXL** High/Low 60/130

Dimensions

2000 Lumen Units: 10.1"H x 13"W x 15"D
3000/4000 Lumen Units 12.3"H x 13"W x 15"D
Shipping Weights: 2000 Lumen 21.5 lbs. (9.8 kg),
3000/4000 Lumen 23.5 lbs. (10.7 kg)

Safety

Stage Interlock, Locks Off Power If Stage is Opened
Automatic Thermal Cutoff Prevents Overheating
UL and C-UL Listed

Accessories (Not Included)

Acetate Roll Brackets, Part# 438-830
50' Acetate Roll, Part# 310-6
Dust Cover, Part# 128-63



DUKANE

Dukane Corporation
Audio Visual Products Division
2900 Dukane Drive
St. Charles, IL 60174
Toll Free (800) 676-2485
Fax (630) 584-5156
e-mail: avsales@dukane.com

SunSplash® is a registered trademark of **DUKANE** Corporation.

*Warranty excludes lamps. Consult Dealer for details.
Form No. 11465-G-02